

Pressure and Temperature Dataloggers

Part of the NOMAD® Family OM-CP-PRTEMP110

\$229
Basic Unit






OM-CP-PRTEMP101 and OM-CP-PRTEMP110 dataloggers shown larger than actual size

- Programmable Start Time
- Measures and Records Pressure and Temperature
- Miniature Size
- User Calibration through Software
- Real Time Operation

The OM-PRTEMP101 and OM-CP-PRTEMP110 are miniature, battery powered, stand-alone, temperature and pressure dataloggers. These dataloggers are a major leap forward in both size and performance. Its real time clock ensures that all data is time and date stamped.

Pressure & Temperature Recorder
Range:
0 to 30 psia
-40°C to 70°C

OM-CP-PRTemp101



The storage medium is non-volatile solid state memory, providing maximum data security even if the battery becomes discharged. Its small size allows it to fit almost anywhere. Data retrieval is simple. Plug it into an empty COM port and our easy-to-use software does the rest. The software converts your PC into a real time strip chart recorder. Data can be printed in graphical or tabular format and can be exported to a text or Microsoft Excel file.

Specifications

Temperature Sensor:

semiconductor

Temperature Accuracy:

±0.5°C (0 to 50°C)

Temperature Resolution:

0.1°C

Temperature Range:

-40 to 80°C (-40 to 176°F)

Pressure Sensor: strain gage

Pressure Accuracy:

1% FSR at 25°C

Pressure Resolution:

0.002 psia

Pressure Range:

0 psia to 30 psia









Temperature Effect on Pressure Span/Offset:

Relative to 25°C going from 0 to 50°C; ±2.0% max, ± 0.4% typical

Temperature/Pressure
Calibration: Digital calibration

is available through software Calibration Date:

Automatically recorded within device to alert user when calibration is required **Recording Interval:**

2 sec to 12 hours selectable

through software

Memory:

OM-CP-PRTEMP101: 8192 rdgs/channel

OM-CP-PRTEMP110: 16,383

rdgs/channel

Start Time: Start time and date are programmable through software

Real Time Recording:

Device may be used with PC to monitor and record data in real time

Red Visual Indicator: LED flashes at selected reading rate or at 1 sec rate under alarm condition

Power: 3.6 V lithium battery

Battery Life:

OM-CP-PRTEMP101: 1 year at 1 min reading rate OM-CP-PRTEMP110: 10 years at 15 min reading rate

Time Accuracy: ±1 minute/month when RS-232 port is not in use

Data Format: Date and time stamped, °C, °F, °K, °R, psia, in Hg, mmH, bar, atm, Torr, Pa, kPa, MPa Weight: OM-CP-PRTEMP101:

30 g (1 oz)

OM-CP-PRTEMP110:

60 g (2 oz)

Computer Interface:

PC serial, RS-232C COM or USB (interface cable required)

Communications: OM-CP-PRTEMP101:

2400 baud

OM-CP-PRTEMP110:

57600 baud

Software: Windows 95/98/NT/2000/XP

Operating Environment: -40 to 80°C (-40 to 176°F) 0 to 95% RH non-condensing

Dimensions:

OM-CP-PRTEMP101: 36 H x 56 W x 16 mm D (1.4 x 2.2 x 0.6") OM-CP-PRTEMP110: 43 H x 43 W x 20 mm D (1.7 x 2.7 x 0.8")

ALL MODELS AVAILABLE FOR FAST DELIVERY!

To Order (Specify Model Number)		
Model No.	Price	Description
OM-CP-PRTEMP101	\$229	Pressure and temperature datalogger with 1-year battery life
OM-CP-PRTEMP101-CERT	229	Pressure and temperature datalogger with 1-year battery life with NIST calibration certificate
OM-CP-PRTEMP110	329	Pressure and temperature datalogger with 10-year battery life with NIST calibration certificate
OM-CP-PRTEMP110-CERT	329	Pressure and temperature datalogger with 10-year battery life
OM-CP-IFC110	99	Windows software and 1.2 m (4') RS-232 cable with DB9F termination
OM-CP-IFC200	119	Windows software and 3.7 m (12') USB interface cable
OM-CP-BAT101	10	Replacement 3.6 V lithium battery for OM-CP-PRTEMP101
OM-CP-BAT105	12	Replacement 3.6 V lithium battery for OM-CP-PRTEMP110

Operator's manual and RS-232 cable are included with the **OM-CP-IFC110** Windows software (software is required to operate the datalogger and is sold separately). NIST calibration for temperature only.

Ordering Example: OM-CP-PRTEMP101-CERT pressure and temperature datalogger with NIST calibration certificate and **OM-CP-IFC110** Windows software and RS-232 cable, \$229 + 60 + 99 = **\$388**.

Your One-Stop Source for Process Measurement and Control!

One Omega Drive | Stamford, CT 06907 | 1-888-TC-OMEGA (1-888-826-6342) | info@omega.com

www.omega.com



UNITED STATES

www.omega.com 1-800-TC-OMEGA Stamford, CT.

CANADA

www.omega.ca Laval(Quebec) 1-800-TC-OMEGA

GERMANY

www.omega.de Deckenpfronn, Germany 0800-8266342

UNITED KINGDOM

www.omega.co.uk Manchester, England 0800-488-488

FRANCE

www.omega.fr Guyancourt, France 088-466-342

CZECH REPUBLIC

www.omegaeng.cz Karviná, Czech Republic 596-311-899

BENELUX

www.omega.nl Amstelveen, NL 0800-099-33-44



More than 100,000 Products Available!

Temperature

Calibrators, Connectors, General Test and Measurement Instruments, Glass Bulb Thermometers, Handheld Instruments for Temperature Measurement, Ice Point References, Indicating Labels, Crayons, Cements and Lacquers, Infrared Temperature Measurement Instruments, Recorders Relative Humidity Measurement Instruments, RTD Probes, Elements and Assemblies, Temperature & Process Meters, Timers and Counters, Temperature and Process Controllers and Power Switching Devices, Thermistor Elements, Probes and Assemblies, Thermocouples Thermowells and Head and Well Assemblies, Transmitters, Wire

Flow and Level

Air Velocity Indicators, Doppler Flowmeters, Level Measurement, Magnetic Flowmeters, Mass Flowmeters, Pitot Tubes, Pumps, Rotameters, Turbine and Paddle Wheel Flowmeters, Ultrasonic Flowmeters, Valves, Variable Area Flowmeters, Vortex Shedding Flowmeters

pH and Conductivity

Conductivity Instrumentation, Dissolved Oxygen Instrumentation, Environmental Instrumentation, pH Electrodes and Instruments, Water and Soil Analysis Instrumentation

Data Acquisition

Auto-Dialers and Alarm Monitoring Systems, Communication Products and Converters, Data Acquisition and Analysis Software, Data Loggers Plug-in Cards, Signal Conditioners, USB, RS232, RS485 and Parallel Port Data Acquisition Systems, Wireless Transmitters and Receivers

• Pressure, Strain and Force

Displacement Transducers, Dynamic Measurement Force Sensors, Instrumentation for Pressure and Strain Measurements, Load Cells, Pressure Gauges, Pressure Reference Section, Pressure Switches, Pressure Transducers, Proximity Transducers, Regulators, Strain Gages, Torque Transducers, Valves

Heaters

Band Heaters, Cartridge Heaters, Circulation Heaters, Comfort Heaters, Controllers, Meters and Switching Devices, Flexible Heaters, General Test and Measurement Instruments, Heater Hook-up Wire, Heating Cable Systems, Immersion Heaters, Process Air and Duct, Heaters, Radiant Heaters, Strip Heaters, Tubular Heaters